

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039635 A2

(51) International Patent Classification⁷: **B60R 9/06**

(21) International Application Number:
PCT/IB2003/004773

(22) International Filing Date: 28 October 2003 (28.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/422,551 31 October 2002 (31.10.2002) US

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: PEDRINI, Fabio [IT/IT]; Via Zamboni 1/Scala-A, Piano-1, Interno-3, I-40125 Bologna (IT).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE-MOUNTED EQUIPMENT CARRIER



WO 2004/039635 A2

(57) Abstract: An equipment carrier for mounting onto a rear component of a vehicle structure, such as a vehicle trunk lid or door, comprises a frame having lower engagement elements engageable with a lower area of the vehicle component, a structure connected to the frame for carrying one or more items of equipment, at least one vehicle engaging member, connected to the frame, for engaging the vehicle component at a position above said lower area, a strap member having upper engagement elements for engagement with an upper area of the vehicle component, and at least one support connected to the frame, provided with a strap engaging and tensioning mechanism, which is engaged by the strap member and can be controlled for tensioning the strap member in order to tighten the upper and lower engagement elements onto the upper and lower areas of the vehicle component.